

	P350P2	P400E2
380-415V, 50Hz	350,0 280,0	400,0 320,0
220/127V, 60 Hz	-	-

0,8

- P350P2
- ()
- 1 12 10%
- P400E2
- ()
- () ISO

8528-3).

	Perkins 2306C-E14TAG2	
	LL6114B	
- / :	6 /	
: ()	14,6 (890,9)	
/ : ()	137,0 (5,4)	
:	15.9:1	
:	T	
:	50	60
:	1500 /	-
: ()	353,0 (473,0)	-
: (/)	1935,0 (280,7)	-
: / (/)	8,3 (27,2)	-
() :	791 (209,0)	-
P350P2 : (/)	74,4 (19,7)	-
P400E2 : (/)	85,8 (22,7)	-
(/) :	291,0 (16549)	-
(/) :	135,0 (7677)	-
(/) :	17,0 (967)	-
: ° (°F)	494 (921)	-
: 3/ (/)	444,0 (15680)	-
	50°C (122°F)*	
3/ (/) :	32,0 (1130)	-
3/ (/) :	66,6 (2352)	-

* FG Wilson

()	()	()	()	()
3601 (141,8)	1110 (43,7)	2070 (81,5)	3316 (7311)	3366 (7421)

ISO 8528, ISO 3046, IEC 60034, BS5000 NEMA MG-1/22.



www.FGWilson.com



Aa

P350P2 / P400E2



FG Wilson

FG Wilson ()

FG Wilson

www.FGWilson.com

